

basic information	Code	X5019
	Cab type	Single
	product model	HFC1073EV2
	Left or right driver	L
	applicable temperature	'-5-40°C
vehicle parameters	length/width/height (mm)	—
	chassis dimension (mm)	/
	wheelbase (mm)	3845
	tire type	215/75 R17.5
	GVW (kg)	5500
	front/rear axle rated payload (kg)	3100/5500
	Rear axle ratio	/
	leaf spring number	3/6+7
	Curb Weight (Kg)	3200
vehicle performance	range underC-WTVC (km)	≥145
	Max speed (km/h)	≥90
	max gradability(%)	≥20
powertrain system	driving motor type	permanent magnet synchronous motor
	motor model	TZ368XSM726F
	rated-peak power (kW)	65/130
	rated -power rotational speed (rpm)	1500/4500
	rated-peak torque (N.m)	415/1200
cooling method	liquid cooling	
electric power system	battery type	lithium iron phosphate battery
	single cell type	173Ah-1P40S
	rated voltage of the battery (V)	515.2
	battery capacity (Ah)	173
	total capacity (kWh)	89.13
weight of the battery (kg)	580	
Suspension	Front Suspension	fewer springs of front cross-section + double acting shock absorber
	Rear Suspension	rear leaf spring suspension (multi spings)+double acting shock absorber
Frame	Frame Cross Section Size	214*70*5
Brake	Type	air brake
	Brake type	front disc, rear drum
	ABS	•
	ASR	•

15 YEARS

Successful Business



100% ELECTRIC

# JAC E N 55

სენა ავტო

SENA AUTO

პირდაპირი ხარისხით

	ESC	•
	HSA	•
	EPB	•
	braking energy recovery	•
	front/rear fog lamp	•
	daytime running light	•
	Widening frame rearview mirror	•+blind area visibility
	electrical heating rearview mirror	•
	power window	•
	application body interface	•
	wind deflector	○
	Interior	roof storage (driver+co-driver)
storage		•
driver sun visor		•
co-driver sun visor		•
flock seats		•
MP5		•
cigarette lighter		•
integraltpe roof		•
safety	driver's safety belt with adjustable height	•
	three-point safety belt for co-driver	•
	driver safety belt warning	•
	co-drivr safety belt warning	•
	auto unlock upon collision	•
	drive recorder	Reserved line speed interface
	Reversing radar	•
	rearview camera	•
	reverse gear buzz	•
power master switch	•	
comfort configurations	AC	•
	CCS	•
	central locking	•
	mechanical foldable remote control key	•
	USB interface	•
	360° vedio	•
charging	charging standard	CCS Type 2
	AC charging	•
	AC charging(slow charging) (h)	16
	DC charging (fast charging)	•
	DC charging (fast charging≥90kW) time (h)	2

15 YEARS

Successful Business



Successful Business